

SPECIFICATION FOR DRIZIT® CLAY GRANULES



	0399	0399/16
Colour	Grey	Grey
Pack Wt (gross)	13 kg	16 kg
Pack Volume	15 litres	20 litres
Pack Size	50 x 35 x 10 cm	45 x 60.5 x 10.5 cm
Qty per pallet	91	70
Sorbency (pack)	8 - 13 litres	10 - 17 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain.

- Composition:** Calcium Sulphate (gypsum) >90%
- Particle Size:** 1 – 5mm (typical)
- Pack Type:** Bag
- Compatibility:** May be safely used with non-aggressive aqueous solutions and liquids immiscible with water, such as hydrocarbons, solvents, mineral oils.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
- Fire Resistance:** Non-combustible.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Refer to our Safety Data Sheet.
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018